

weberfloor Polish Sealer 5523



weberfloor Polish Sealer 5523 is a durable, gloss sealer that boosts stain and chemical resistance on interior/exterior concrete surfaces. Suitable for polished, decorative, or Weberfloor PUR Décor floors, it enhances appearance and protects against spills without yellowing.

Technical Data Sheet

Issued on : 2025 January 17

TECHNICAL DATA

Color	Clear, Gloss Level 60%-80%
SG-Mix	Approx. 1.05 gr/ml
Drying time	Touch Dry : 30-60 Minutes Light Traffic : 4 Hours Normal Traffic : 12 Hours

Packaging

Packaging of

- 20 Kg/Pail
- 5 Kg/Pail

Shelf life

At least 12 months when stored cool and dry.

Substrate of Application

This product can be applied to existing, cured concrete of any age, including:

- Terrazzo floors
- Warehouses
- Workshops
- Depots and loading bays
- Factory floors
- Interior and exterior surfaces

Product advantages

- Low odor and easy application
- Durable, long-lasting protective shine
- Enhances cleaning efficiency and reduces maintenance costs
- Provides an attractive, hygienic finish

- Maintains slip resistance
- UV stable – resistant to yellowing, discoloration, and peeling

APPLICATION METHOD

1. Substrate Application

- weberfloor Polish Sealer 5523 Clear can be applied to cured concrete of any age. Surfaces must be clean, structurally sound, and free from contaminants such as grease, oil, or debris.

2. Application

- Suitable for broomed, steel-troweled, honed, or polished interior concrete surfaces.
- Lightly dampen a clean microfiber pad with the product.
- Spray weberfloor Polish Sealer 5523 using a clean pump sprayer with a 0.1 gpm conical or fan tip, working section by section (e.g., between control joints).
- Spread evenly using the damp microfiber pad, maintaining a thin, uniform coat. Avoid overlaps and stop once drying begins.
- Allow to dry tack-free (typically 20–60 minutes), then repeat for a second coat. Recommended coverage: 0.2 kg/m² total.
- For enhanced gloss, burnish with a high-speed machine and white polishing pad after the final coat has dried (minimum 60 minutes).
- Protect from water exposure for at least 4 hours.

Constraints / Pay attention

Keep away from heat, sparks, and open flames. Avoid breathing vapors and contact with skin and eyes. Keep containers closed and store in a cool, ventilated area when not in use. Proper ventilation and protective measures must be provided during mixing, application, and drying to maintain safe vapor concentrations and protect against toxic hazards. Use necessary safety equipment and carefully observe ventilation requirements, especially in confined or enclosed spaces such as tank interiors and buildings.

SAINT-GOBAIN INDONESIA

Sequis Tower Level 15, Jl. Jend. Sudirman Kav. 71, RT.5/RW.3,

Senayan, Kebayoran Baru, Jakarta Selatan 12190

Office: 021-27099600

Email: CS.Indonesia@saint-gobain.com

Website: mortartutama.com | LinkedIn: Saint-Gobain Indonesia

ISO 14001:2015 Certified

